

Discussion Topics

This section of ClearCase covers the custom scripts developed for Ir1.

• Custom scripts use the directory /usr/ccase which is mounted by each ClearCase client so that it can access all scripts

Add a User-Specified Label



/usr/ccase/scripts/add_label.sh

Description:

Script will attach the given label to all specified elements

Usage:

add_label.sh [-r] label element... add_label.sh -h

-h: output this help message and exit

520-TD-001-002

M&O 2-2

Discussion Topics

/usr/ccase/scripts/add_label.sh

Description:

Adds a user-specified label to all specified elements. Optionally processes sub-directories.

Display Backup File Status



/usr/ccase/scripts/backup_stat.sh

Description:

Display the status file generated by the backup_all.sh script

Usage:

backup_stat.sh backup_stat.sh -h

-h: output this help message and exit

520-TD-001-002


M&O 2-3

Discussion Topics

/usr/ccase/scripts/backup_stat.sh

Description:

Display the status file generated by the backup_all.sh script.



Discussion Topics

/usr/ccase/scripts/backup_view.sh

Description:

This script is used to automatically perform the operation of backing up a view.

Backup All VOBs and Views



/usr/ccase/scripts/backup_vob.sh

Description:

Backup all VOBs and Views

Usage:

backup_vob.sh backup_vob.sh -h

-h: output this help message and exit

520-TD-001-002

M&O 2-5

Discussion Topics

/usr/ccase/scripts/backup_vob.sh

Description:

Backup all VOBs and Views.

Prevent Use of ClearCase Command



/usr/ccase/scripts/block_rmbranch.sh

Description:

Script that is part of a ClearCase trigger to block execution of the command 'rmbranch'

520-TD-001-002

M&O 2-6

Discussion Topics

/usr/ccase/scripts/block_rmbranch.sh

Description:

Trigger script to prevent the use of the cleartool command "rmbranch", except by authorized users.

Prevent Use of ClearCase Command (cont'd)



/usr/ccase/scripts/block_rmelem.sh

Description:

Script that is part of a ClearCase trigger to block execution of the command 'rmelem'

520-TD-001-002

M&O 2-7

Discussion Topics

/usr/ccase/scripts/block_rmelem.sh

Description:

Trigger script to prevent the use of the cleartool command "rmelem", except by authorized users.

Prevent Use of ClearCase Command (cont'd)



/usr/ccase/scripts/block_rmver.sh

Description:

Script that is part of a ClearCase trigger to block execution of the command 'rmver'

520-TD-001-002

M&O 2-8

Discussion Topics

/usr/ccase/scripts/block_rmver.sh

Description:

Trigger script to prevent the use of the cleartool command "rmver", except by authorized users.

Check-in All Files



/usr/ccase/scripts/checkin_all.sh

Description:

Script that checks in all elements in the specified directory. If the -r option is included, subdirectories will also be processed.

Usage:

checkin_all.sh [-r] directory
checkin_all.sh -h

-h : output this help message and exit

M&O 2-9

Discussion Topics

/usr/ccase/scripts/checkin_all.sh

Description:

Check in all files in a specified directory. Optionally processes sub-directories

Checkout All Files



/usr/ccase/scripts/checkout_all.sh

Description:

Script that checks out all elements in the specified directory.

If the -r option is included, subdirectories will also be processed.

Usage:

checkout_all.sh [-r] directory
checkout_all.sh -h

-h: output this help message and exit

520-TD-001-002

M&O 2-10

Discussion Topics

/usr/ccase/scripts/checkout_all.sh

Description:

Check out all files in a specified directory. Optionally processes sub-directories.

List All Elements with a Specified Label



/usr/ccase/scripts/list_label.sh

Description:

Script that lists all elements that have the label attached

Usage:

list_label.sh label list_label.sh -h

-h: output this help message and exit

520-TD-001-002

M&O 2-11

Discussion Topics

/usr/ccase/scripts/list_label.sh

Description:

List all elements that have a specified label attached.

Create a Directory for Scripts



/usr/ccase/scripts/make_dirs.sh

Description:

Script that creates the directory structure for the science software VOBs

Usage:

make_dirs.sh make_dirs.sh -h

520-TD-001-002

M&O 2-12

Discussion Topics

/usr/ccase/scripts/make_dirs.sh

Description:

Creates the directory structure necessary for these scripts.

Create a VOB



/usr/ccase/scripts/make_vob.sh

Description:

Script that creates a VOB, initializes it with Labels and Triggers, and creates a default View for VOBADM

Usage:

make_vob.sh vobname make_vob.sh -h

-h: output this help message and exit

M&O 2-13

Discussion Topics

/usr/ccase/scripts/make_vob.sh

Description:

Creates a VOB. Also creates a View for VOBADM, if necessary. Adds pre-defined triggers, labels, and attributes to the VOB.

Change Ownership of New Elements



/usr/ccase/scripts/mkelem_chown.sh

Description:

This script is part of a trigger on the ClearCase command 'mkelem'. It changes the owner to VOBADM, and sets the permissions to rwxrwxr-x.

- This is done to ease Administration headaches.

Usage:

None

520-TD-001-002

M&O 2-14

Discussion Topics

/usr/ccase/scripts/mkelem_chown.sh

Description:

Trigger that changes the ownership of new elements to VOBADM. Also changes the permissions to "770"